

# BP818

## Magnetic Coupler Isolator


---

### Description

The BP818 is a magnetically coupled isolator for communication between primary and secondary power supplies.

The BP818 has two built-in coupling coils and magnetic coupling to provide galvanic isolation. The BP818 offers reliable performance eliminating the disadvantages of traditional optocouplers such as low precision, nonlinear current transfer ratio, as well as limited bandwidth. The BP818 operates without bias current on primary and secondary sides, which greatly reduces system standby power consumption. In combination with the corresponding primary and secondary control ICs, it can establish a high-performance switching power supply total solution.

The BP818 meets the global safety requirements for reinforced insulation. It utilizes an LSOP-4 package with a creepage distance of 8mm and isolation voltage up to 1000VAC. Certified by UL62368, TUV (IEC62368), CQC (GB4943.1), and VDE (IEC60747) for safety regulations.



LSOP-4 package

### Applications

- QC / USB
- Adapters
- AC/DC auxiliary power

BPS Co

## Disclaimer

The information provided in this datasheet is believed to be accurate and reliable. However, Bright Power Semiconductor (BPS) reserves the right to make changes at any time without prior notice.

No license, to any intellectual property right owned by BPS or any other third party, is granted under this document. BPS provides information in this datasheet AS IS and with all faults, and makes no warranty, express or implied, including but not limited to, the accuracy of the information provided in this datasheet, merchantability, fitness of a specific purpose, or non-infringement of intellectual property rights of BPS or any other third party. BPS disclaims any and all liabilities arising out of this datasheet or use of this datasheet, including without limitation consequential or incidental damages.